

INI MPPT		20A	30A	40A	50A	60A
Product category	Controller Properties	MPPT (maximum power point tracking)				
	MPPT efficiency	≥99.5%				
	Standby power	0.5W~1.2W				
	System voltage	Automatic recognition				
	Heat-dissipating method	Intelligent fan cooling				
Input Characteristics	Max.PV input voltage(VOC)	DC150V				
	Start the charge voltage point	Battery voltage + 3V				
	Low input voltage protection point	Battery voltage + 2V				
	Over voltage protection point	DC150V				
	Rated PV power	12V system	260W	390W	520W	650W
Charge Characteristics	24V system	520W	780W	1040W	1300W	1560W
	36V system	780W	1170W	1560W	1950W	2340W
	48V system	1040W	1560W	2080W	2600W	3120W
LOAD Characteristics	Selectable Battery Types (Default Gel battery)	Sealed lead acid, Gel battery, Flooded (Other types of the batteries also can be defined)				
	Charge rated current	20A	30A	40A	50A	60A
	Charge Method	3-Stage: constant current(fast charging)-constant voltage-floating charge				
Display & Communication	Load voltage	The same as the battery voltage				
	Load rated current	40A			60A	
	Load control mode	On\Off mode, PV voltage control mode, Dual-time control mode, PV + Time control mode				
Other Parameters	Display mode	High-definition LCD segment code backlight display				
	Communication mode	8-pin RJ45 port/RS485/support PC software monitoring/ support WiFi module to realize APP cloud monitoring				
	Protect function	Input-output over \ under voltage protection, Prevention of connection reverse protection,battery shedding protection etc.				
Other Parameters	Operation Temperature	-20°C~+50°C				
	Storage Temperature	-40°C~+75°C				
	IP(Ingress protection)	IP21				
	Max. connection size	20mm2			30mm2	
	Net Weight (kg)	2.3			2.6	
	Gross Weight (kg)	3			3.5	
	Product Size (mm)	240*168*66			270*180*85	
Packing Size(mm)		289*204*101			324*223*135	